

# Soluciones HMI y Networking para entornos adversos

Helping   
Innovation

### Tablets y Laptop Robustos:

Anatronic ofrece un amplio abanico de Tablets y Laptop de alta calidad y rugerizados, necesarios en aquellos entornos adversos como son Mineras, Obra Civil, Defensa etc..



#### **SA14iT**

- 14" Semi-Rugged Laptop
- IP53 & MIL-STD 810G 3 feet drop
- Sunlight Readable (500 nits) & Resistive touch panel
- Night Vision Mode & Backlit Keyboard
- Long Battery Life : 9 cell 7800mAh and Optional 2nd battery pack(6 cell 5200 mAh)



#### **U12CI**

- 12" Semi-Rugged Convertible Notebook :
- Convertible for both Tablet and Notebook
- Long Battery Life : 8hrs (with 2nd battery)
- MIL-STD-810G 4 feet
- Spill Proof : Keyboard, Touch, Buttons



#### T7Q

- Industrial rugged 7" Tablet PC for Industrial :
- MIL-STD-810G ( 5 feet ) & IP65 waterproof
- Sunlight Readable
- Long Battery Life (around 10hrs with 2 battery packs)
- Vehicle Dock available for T7Q with external antenna I/O port



#### CA10CT :

- 10.1" Semi-Rugged Tablet PC
- IP43 & 4 feet drop
- Multi-Touch and MSR, Smart Card Reader...
- Long Battery Life
- with Intel Cedar View N2600



### BE905-A1

- 1.0 GHz ARM Cortex A8 CPU Core Support SD/SDHC Card
- 7" TFT LCD with 800x480 WVGA
- 2x ADC/ 1x CAN Bus/ 7x User Programmable Keypads
- Internal 2 Watt Speaker and Microphone
- DC 11V~30V Power supply
- 512MB LPDDR/8GB eMMC
- Windows CE 6.0 OS
- 4-wired Resistive Touch Panel
- On-board 3G and GPS Module
- 1x RS232C/ 1x Host USB/ 1x Device USB/4x GPIO
- 18.5Wh Li-on Battery (optional)



### BE903-A

- 400MHz 32bit RISC architecture ARM926EJ CPU Core
- 2GB NAND Flash/64MB DDR2 DRAM
- WINCE 5.0 OS
- 8 interrupt-based keypads
- 8 x IO/ 1 x Host USB/ 1 x Device USB/ 3 x RS232
- On-board GSM/GPRS and GPS modul
- 7" TFT 16:9 display with 800 x 480 resolution
- 4-wire resistive touch panel interface (option)
- DSP based audio codec via IIS-bus
- Built-in 2W amplifier/earphone
- Support SD/HS-MMC card
- 9V~28V DC requirement



### APC-3098A

- Intel Atom Z5XXP CPU support
- Fanless Design
- Resistive touch option
- Total IP65
- Wide range DC 9~32V



### APC-3593P

- Intel Atom N2600 CPU support
- Fanless Design
- Projected capacitive touch
- Total IP65
- Wide range DC 9~32V



### APC-3597B

- Intel Atom N2600 CPU support
- Fanless Design
- Resistive touch or GFG touch option
- Total IP65
- Wide range DC 9~32V



### APC-3791A

- Intel GM45 Socket P Core 2 Duo CPU support
- Fanless Design
- Resistive touch or GFG touch option
- Total IP65
- Wide range DC 11~32V



### IPC924-212-FL

- Fanless
- Atom™ D425/D525
- 1 x LAN
- 6 x USB
- 4 x COM
- 1 x VGA
- 4 x PCI
- 1 x PCIe x1
- 1 x PCIe x16
- 1 x 2,5 HDD SATA
- 1 x Compact Flash



### IPC914-213-FL

- Fanless
- Core™ i7/ i5/ i3
- 2 x LAN
- 6 x USB
- 4 x COM
- 1 x VGA
- 4 x PCI
- 1 x PCIe x1
- 1 x PCIe x16
- 1 x 2,5 HDD SATA
- 1 x Compact Flash



### RBOX610

- Fanless
- iMX-287, ARM9 16-bit RISC
- 1 x USB
- 4 x COM
- 2 x LAN
- 2 x CAN
- Onboard 4GB eMMC
- 1 x SDHC Card
- 12 – 48 V



### RBOX101-6COM

- Fanless
- ATEX
- Intel Atom Z520
- 2 x USB
- 6 x COM
- 2 x LAN
- 1 x VGA
- 4 x DIO
- 1 x Compact Flash Card
- 12 – 48 V



**Rack 19"**

**IGSW-24040T**

Industrial 24-Port 10/100/1000Mbps with 4 Shared SFP Managed Gigabit Switch

**IGSW-2840**

24-Port 10/100Mbps + 4G TP / SFP Combo L2/L4 Industrial Managed Switch



**Carril DIN**

**IGS-10020HPT**

Industrial 8-Port 10/100/1000T 802.3at PoE + 2-Port 100/1000X SFP Managed Switch with Wide Operating Temperature

**IGS-10020MT**

Industrial 8-Port 10/100/1000T + 2 100/1000X SFP Managed Switch





**Carril DIN**  
**IGS-10080MFT**

Industrial 8 100/1000X SFP + 2-Port 10/100/1000T Managed Switch (-40 ~ 75 Degree C)

**IGS-8044MT**

4-Port 10/100/1000Mbps + 4-Port Gigabit TP/SFP Combo Managed Industrial Switch with Wide Operating Temperature



**Carril DIN**  
**ISW-1022MT**

8-Port 10/100Mbps + 2-Port Gigabit TP/SFP Combo Managed Industrial Switch with Wide Operating Temperature

**ISW-1022MPT**

8-Port 10/100Mbps + 2-Port Gigabit TP/SFP Combo PoE Managed Industrial Switch with Wide Operating Temperature

### Anatronic Madrid:

Dirección: [Paseo Imperial N.8, 3 B](#)  
C. Postal:28005 Madrid (España)  
Teléfono:(34)913660159  
Fax:(34)913655095

### Anatronic Barcelona:

Dirección: [C/ Campo Florido 40-46 Esc. A 1 3](#)  
C. Postal:08027 Barcelona (España)  
Teléfono:(34) 932240283  
Fax:(34) 932240279

### Anatronic Bilbao:

Dirección: [C/ Errekagane, 11 3 Dcha.](#)  
C. Postal:48600 Sopelana Vizcaya (España)  
Teléfono:(34) 944636066  
Fax:(34) 944634235

### Anatronic Portugal:

Dirección: [Rua Capitão Leitão, N 26 - 1 Esq](#)  
C. Postal:2800-132 Almada (Portugal)  
Teléfono:(351) 219376267  
Fax:(351) 219371834

### Anatronic Chile:

Dirección: [C/ Badajoz, 100, Of. 1305](#)  
C. Postal: Las Condes, Santiago de Chile  
Teléfono:(+56) 228973598

### Anatronic Online:

[info@anatronic.com](mailto:info@anatronic.com)  
[www.anatronic.com](http://www.anatronic.com)  
<http://sti.anatronic.com>